


Extreme 7520

Highlights

- High-performance, fixed-form switches for leaf, spine, aggregation, or core applications
- Universal dual-persona hardware allows user choice of switch operating systems
- ExtremeCloud™ IQ and ExtremeCloud IQ - Site Engine for powerful, secure and easy to use cloud-based network management.
- Fabric Connect for automated network operations, simplified network provisioning and enhanced security

Key Hardware Features

- Three models – two models with no MACsec and one model with MACsec in a fixed 1U form factor
- AC and DC power options
- Back-to-front and front-to-back airflow options
- Up to 8-unit stacking
- Integrated Application Hosting enables 3rd-party applications without impacting switch performance
- Non-blocking, wire-speed design



Universal Aggregation/Core Switch Platform

The Extreme 7520 are purpose-built 48-port 10Gb and 48-port 25Gb switches designed for high-performance aggregation and core applications. As a universal hardware platform, the 7520 provides end-to-end secure network segmentation, in addition to advanced policy capabilities, with a user-selectable choice of Extreme's flagship switch operating systems. This makes the 7520 a uniquely flexible platform that can be deployed in a variety of aggregation and core environments.

The Extreme 7520 network hardware platform enables organizations to design networks that accommodate a variety of applications and east-west traffic patterns. With its high-density scale-out architecture, leading power efficiency, and airflow options, the 7520 platform delivers a cost-effective solution that optimizes power, cooling, and equipment room space, wherever your network operating center might be.

Three models of the 7520 are available.

7520-48XT-6C

- 48 x 1Gb/10Gb 10GBaseT copper ports (no MACsec)
- 6 x 40Gb/100Gb QSFP28 fiber ports (no MACsec)

7520-48Y-8C

- 48 x 1Gb/10Gb/25Gb SFP28 fiber ports (no MACsec)
- 8 x 40Gb/100Gb QSFP28 fiber ports (no MACsec)

7520-48YE-8CE

- 48 x 10/25Gb SFP28 fiber ports with MACsec support
- 8 x 100Gb QSFP28 fiber ports with MACsec support

Universal Hardware Platform

The 7520 Series comes with a dual-persona capability allowing user choice of the switch operating system (OS). Either the Switch Engine (EXOS) or Fabric Engine (VOSS) persona can be enabled on 7520 hardware models. The desired persona can be selected at start-up or changed at a later stage. Once selected, the 7520 assumes the features/capabilities of the selected OS.

7520 persona activation can be done manually at boot-up, including via the system CLI. Or, it can be automated by pre-provisioning the 7520 persona in ExtremeCloud IQ. When first booted, the 7520 automatically connects to ExtremeCloud IQ to find its persona. The pre-provisioned OS persona is then remotely enabled on the 7520 system – eliminating the need for manual selection.

Ethernet Fabric Services

The 7520 supports a variety of Ethernet Fabric services, including Extreme's Fabric Connect when running Fabric Engine (VOSS) and Extreme's IP Fabric when running Switch Engine (EXOS). It also supports Fabric Attach for automated connection to either Layer 2 or Layer 3 fabric services. Extreme's Fabric Connect and IP Fabric on the 7520 enable the creation of virtualized networks that automate network operations, simplify network provisioning, and enhance security, all while reducing the strain on network and IT personnel.

High-Performance Stacking

Two of the 7520's QSFP28 uplink ports can be used for high-speed 400Gb stacking when running Switch Engine (EXOS). Up to eight systems can be stacked using qualified direct attach cables and/or optical transceivers. (Note: Stacking is not supported when running Fabric Engine (VOSS)).

Management

The 7520 can be managed by ExtremeCloud IQ and ExtremeCloud IQ-Site Engine for comprehensive unified management with a consolidated view of users, devices and applications across wired and wireless networks.

Zero-touch provisioning from ExtremeCloud IQ lets one quickly bring new 7520 switches online as well as enable the selection of the operating system (OS) persona. Alternatively, 7520 on-box management can be done manually via a web-based GUI or generic CLI.

Switch Specifications

Model	7520-48Y-8C 7520-48YE-8CE	7520-48XT-6C
Ports	<ul style="list-style-type: none"> 48 x 1/10/25GbE SFP28 ports (48Y/8C) 48 x 10/25GbE SFP28 ports (48YE-8CE) 8 x 40/100GbE QSFP28 ports 1 x Serial console port RJ-45 1 x 10/100/1000BASE-T out-of-band management port USB Type A storage port 	<ul style="list-style-type: none"> 48 x 1/10GbE 10GBaseT ports 6 x 40/100GbE QSFP28 ports 1 x Serial console port RJ-45 1 x 10/100/1000BASE-T out-of-band management port USB Type A storage port
Power Supplies	<ul style="list-style-type: none"> Modular 800W AC power supply (up to two PSUs) Modular 800W DC power supply (up to two PSUs) Front to Back and Back to Front airflow option 	<ul style="list-style-type: none"> Modular 800W AC power supply (up to two PSUs) Modular 800W DC power supply (up to two PSUs) Front to Back and Back to Front airflow options
Fan Modules	<ul style="list-style-type: none"> 6 fan modules Front-Back and Back-Front airflow options 	<ul style="list-style-type: none"> 6 fan modules Front-Back and Back-Front airflow options
Dimensions	<ul style="list-style-type: none"> 17.3in W/21.24in D/1.7in H (44.0cm/53.95cm/4.3cm) (48Y-8C) 17.3in W/21.69in D/1.7in H (44.0cm/53.95cm/4.3cm) (48YE-8CE) 	<ul style="list-style-type: none"> 17.3in W/20.9in D/1.7in H (44.0cm/53.2cm/4.3cm)
Weight	<ul style="list-style-type: none"> 16.71 lb (7.58 kg) empty chassis (48Y-8C) 22.29 lb (10.11 kg) with two AC PSUs (-F and -R models) (48Y-8C) 20.35 lb (9.23 kg) empty chassis (48YE-8CE) 26.23 lb (11.90 kg) with two AC PSUs (-F and -R models) (48YE-8CE) 	<ul style="list-style-type: none"> 16.34 lb (7.41 kg) no PSU 20.88 lb (9.47 kg) with two AC PSUs (-F and -R models)
Performance	<ul style="list-style-type: none"> Line rate 4 Tbps Switching Capacity (2 Tbps ingress, 2 Tbps egress) Average Latency: 800 ns Forwarding rate: 1000 Mpps 	<ul style="list-style-type: none"> Line rate 2.16 Tbps Switching Capacity (1.08 Tbps ingress, 1.08 Tbps egress) Average Latency: 2,400 ns Forwarding rate: 1000 Mpps
CPU/Memory	<ul style="list-style-type: none"> 8-core Processor 16GB DDR4 ECC memory 128GB SSD memory 	<ul style="list-style-type: none"> 8-core Processor 16GB DDR4 ECC memory 128GB SSD memory
Packet Buffers	32MB	32MB
Environmental Operating Conditions	AC/DC, one fan failed, front-to-back: <ul style="list-style-type: none"> 0°C (32°F) to 50°C (122°F) at sea level; 0°C (32°F) to 40°C (104°F) up to 3000 m (10,000 ft) AC/DC, one fan failed, back-to-front: <ul style="list-style-type: none"> 0°C (32°F) to 45°C (113°F) at sea level; 0°C (32°F) to 40°C (104°F) up to 3000 m (10,000 ft) 	AC/DC, one fan failed, front-to-back: <ul style="list-style-type: none"> 0°C (32°F) to 50°C (122°F) at sea level; 0°C (32°F) to 40°C (104°F) up to 3000 m (10,000 ft) AC/DC, one fan failed, back-to-front: <ul style="list-style-type: none"> 0°C (32°F) to 45°C (113°F) at sea level; 0°C (32°F) to 40°C (104°F) up to 3000 m (10,000 ft)

7520 Software Scaling Values

Switch Engine

MAC Table: 294,000
IPv4 ARP Table: 172,000

IPv4 Route Table: 294,000
IP Multicast Entries (S,G,V): 110,000
IPv6 Neighbor Table: 78,000
IPv6 Route Table: 218,000
ACLs (Ingress/Egress): 38,864/2,048

QoS Egress Queues per port: 8
 VLANs: 4,094
 Routed VLANs: 4,094

One Policy Scaling

Policy Profiles: 63
 Unique Permit/Deny Rules per switch: 16,312

Fabric Engine

MAC Table: 164,000
 IPv4 ARP Table: 65,536
 IPv4 Route Table: 24,576
 IP Multicast Entries (S,G,V): 6,000

IPv6 Neighbor Table: 32,768
 IPv6 Route Table: 12,288
 ACLs (Ingress/Egress): 8,192/6,144
 QoS Egress Queues per port: 8
 VLANs: 4,059
 IP Interfaces (Routed VLANs): 1,000

Fabric Connect Scaling

Fabric Adjacencies per switch: 255
 Fabric nodes per area (BEB + BCB): 1,000
 BEB Nodes per VSN: 2,000
 L2 VSNs: 4,000
 L3 VSNs: 256

Power and Heat Dissipation

Switch Model	Minimum Heat Dissipation (BTU/hr) (Idle, no ports linked)	Minimum Power Consumption (W) (Idle, no ports linked)	Maximum Heat Dissipation (BTU/hr) (Fans high, all ports 100% traffic)	Maximum Power Consumption (W) (Fans high, all ports 100% traffic)
7520-48YAC	553 BTU/hr	167W	1600 BTU/hr	469W
7520-48YDC	553 BTU/hr	167W	1600 BTU/hr	469W
7520-48XTAC	642 BTU/hr	194W	1225 BTU/hr	359W
7520-48XTDC	642 BTU/hr	194W	1225 BTU/hr	359W

Power Supply Specifications

	800W AC PSU XN-ACPWR-800W-F/R	800WDC PSU XN-DCPWR-800W-F/R
Dimensions	3.15 in W x 1.57 in H x 8.11 in D (8.0 cm x 4.0 cm x 20.6 cm)	3.15 in W x 1.57 in H x 8.11 in D (8.0 cm x 4.0 cm x 20.6 cm)
Weight	1.79 lb (0.81kg)	1.85 lb (0.85kg)
Voltage Input Range	100VAC-140 VAC/200VAC-240 VAC	-48VDC to -60VDC
Line Frequency Range	50Hz– 60Hz	N/A
PSU Input Socket	IEC320 C14	Terminal Block
PSU Output Cord	IEC320 C13	N/A
Operating Conditions	0°C–55°C operation	0°C–55°C operation

Environmental

Environmental Specifications

EN/ETSI 300 019-2-1 v2.1.2 - Class 1.2 Storage
 EN/ETSI 300 019-2-2 v2.1.2 - Class 2.3 Transportation
 EN/ETSI 300 019-2-3 v2.1.2 - Class 3.1e Operational
 EN/ETSI 300 753 (1997-10) - Acoustic Noise
 ASTM D3580 Random Vibration Unpackaged 1.5 G

Environmental Compliance

EU RoHS - 2011/65/EU
 EU WEEE - 2012/19/EU
 EU REACH – Regulation (EC) No 1907/2006 Reporting
 China RoHS - SJ/T 11363-2006
 Taiwan RoHS - CNS 15663(2013.7)

Environmental Operating Conditions

Temp: 0°C to 50°C (32°F to 122°F)

Humidity: 10% to 95% relative humidity, non-condensing

Altitude: 0 to 3,000 meters (9,850 feet)

Shock (half sine) 30m/s² (3G), 11ms, 60 shocks

Random vibration: 3Hz to 500Hz at 1.5 G rms

Packaging and Storage Specifications

Temp: -40°C to 70°C (-40°F to 158°F)

Humidity: 10% to 95% relative humidity, non-condensing

Packaged Shock (half sine): 180 m/s² (18 G), 6 ms, 600 shocks

Packaged Vibration: 5Hz to 62Hz at velocity 5 mm/s, 62Hz to 500Hz at 0.2 G

Packaged Random Vibration: 5Hz to 20Hz at 1.0 ASD w/-3 dB/oct. from 20Hz to 200Hz

Packaged Drop Height: 14 drops minimum on sides and corners at 42 inches (<15 kg box)

Regulatory and Safety

North American ITE

UL60950-1

UL/CuL62368-1 Listed

CSA 22.2 No. 60950-1 2nd edition 2014 (Canada)

Complies with FCC 21CFR 1040.10 (U.S. Laser Safety)

CDRH Letter of Approval (US FDA Approval)

European ITE

EN 60950-1 2nd Edition

EN62368-1

EN 60825-1 Class 1 (Lasers Safety)

2014/35/EU Low Voltage Directive

International ITE

CB Report & Certificate per IEC 60950-1

CB Report & Certificate IEC 62368-1

AS/NZS 60950-1 (Australia/New Zealand)

EMI/EMC Standards

North American EMC for ITE

FCC CFR 47 Part 15 Class A (USA)

ICES-003 Class A (Canada)

European EMC Standards

EN 55032 Class A EN55024

EN 61000-3-2,2014 (Harmonics)

EN 61000-3-3 2013 (Flicker)

EN 300 386 (EMC Telecommunications) 2014/30/EU EMC Directive

International EMC Certifications

CISPR 32, Class A (International Emissions) AS/NZSCISPR32

CISPR24 Class A (International Immunity)

IEC 61000-4-2/EN 61000-4-2 Electrostatic Discharge, 8 kV Contact, 15 kV Air, Criteria B

IEC 61000-4-3/EN 61000-4-3 Radiated Immunity 10V/m, Criteria A

IEC 61000-4-4/EN 61000-4-4 Transient Burst, 2 kV, Criteria B

IEC 61000-4-5/EN 61000-4-5 Surge, 2 kV L-L, 2 kV L-G, Level 3, Criteria B

IEC61000-4-6 Conducted Immunity, 0.15-80MHz, 10V/rms, 80%AM (1kHz), Criteria A

IEC/EN61000-4-11 Power Dips & Interruptions, >30%, 25 periods, Criteria C

Country Specific

VCCI Class A (Japan Emissions)

ACMA RCM (Australia Emissions)

CCC Mark (China)

KCCMark, EMC Approval (Korea)

BSMI (Taiwan)

Anatel (Brazil)

NoM (Mexico)

EAC (Russia, Belarus, Kazakhstan)

NRCS (South Africa)

IEEE802.3 Media Access Standards

IEEE 802.3ab 1000BASE-T

IEEE 802.3ae 10GBASE-X

IEEE 802.3 10GBASE-T (up to 100m using Cat6a cabling or better)

IEEE802.3by-2016 25Gb/s Operation

IEEE 802.3ba/802.3bm 40 GBASE-X and 100 GBASE-X

IEEE 802.3az Energy Efficient Ethernet (7520-48XT only)

Ordering Notes

Customers ordering an AC-bundled version of the 7520 Series switch receive the hardware switch along with a Base software license, integrated power supply, fan modules, and rack-mount kit.

Customers ordering a non-bundled version of the 7520 Series switch customers will only receive the hardware switch, Base software license, and rackmount kit. Customers in this case, must order Power Supply Units (PSU) and fan modules separately.

At least one Power Supply Unit (PSU) is required for 7520 operations. Additional power supplies, transceiver/optics, power cords, as well as Premier and/or MACsec licenses, must be ordered separately.

Base Software and Optional Premier License

The Base software included with each 7520 unit supports most available software features. Certain features, however, require a Premier License to operate:

For Switch Engine, a Premier License is required for:

- 5 or more OSPF interfaces
- PIM DM/PIM SSM
- Anycast RP (Rendezvous Point)
- MultiSource Discovery Protocol (MSDP)
- IS-IS/BGP4/MBGP*
- GRE Tunneling
- Ethernet VPN (EVPN)

* Up to 2 BGP interfaces included in Base software

For Fabric Engine, a Premier License is required for :

- Layer 3 Virtual Services Networks (VSNs)
- Distributed Virtual Routing Controller
- VXLAN Gateway
- 5 or more active OSPF interfaces

17 or more BGP peers

Insight Architecture/Integrated Application Hosting (IAH)

Power Supplies for Use with Your Switch

Each 7520 Series switch runs with two replaceable internal power supply modules that provide all of the power needed for the switch to operate. You can remove one power supply module without interrupting the switch's operation. Supported power supply configurations include two 750W AC power supply modules, two 750W DC power supply modules, or one 750W AC and one 750W DC power supply module. Power supply modules have integrated cooling fans that operate independently of the switch fans and are available with front-to-back or back-to-front airflow. The direction of the airflow in both power supply modules must be in the same direction and must also be in the same direction of the airflow in the fan modules.

Ordering Information

Part Number	Product Name	Description
7520-48XT-6C	7520-48XT Base System	Extreme 7520-48XT Switch - Ships with two empty power supply slots, six empty fan slots, one 4-post rack mount kit. Supports 48 x 1G/10G copper ports and 6 x 40G/100G fiber ports
7520-48XT-6C-AC-F	7520-48XT with front-to-back airflow	Extreme 7520-48XT Switch - Ships with two AC front-to-back airflow power supplies, six front- to-back airflow fans, one 4-post rack mount kit. Supports 48 x 1G/10G copper ports and 6 x 40G/100G fiber ports
7520-48XT-6C-AC-R	7520-48XT with back-to-front airflow	Extreme 7520-48XT Switch - Ships with two AC back-to-front airflow power supplies, six back- to-front airflow fans, one 4-post rack mount kit. Supports 48 x 1G/10G copper ports and 6 x 40G/100G fiber ports
7520-48Y-8C	7520-48Y Base System	Extreme 7520-48Y Switch with two empty power supply slots, six empty fan slots, Ships with one 4-post rack mount kit. Supports 48 x 1G/10G/25G fiber ports and 8 x 40G/100G fiber ports
7520-48YE-8CE	7520-48YE Base System	Extreme 7520-48YE Switch with two empty power supply slots, six empty fan slots, Ships with one 4-post rack mount kit. Supports 48 x 10G/25G fiber ports and 8 x 40G/100G fiber ports. Includes embedded MACsec capabilities.
7520-48Y-8C-AC-F	7520-48Y with front- to-back airflow	Extreme 7520-48Y Switch - Ships with two AC front-to-back airflow power supplies, six front- to-back airflow fans, one 4-post rack mount kit. Supports 48 x 1G/10G/25G fiber ports and 8 x 40G/100G fiber ports
7520-48YE-8CE-AC-F	7520-48YE with front-to-back airflow	Extreme 7520-48YE Switch - Ships with two AC front-to-back airflow power supplies, six front- to-back airflow fans, one 4-post rack mount kit. Supports 48 x 10G/25G fiber ports and 8 x 40G/100G fiber ports. Includes embedded MACsec capabilities.

Part Number	Product Name	Description
7520-48Y-8C-AC-R	7520-48Y with back- to-front airflow	Extreme 7520-48Y Switch - Ships with two AC back-to-front airflow power supplies, six back- to-front airflow fans, one 4-post rack mount kit. Supports 48 x 1G/10G/25G fiber ports and 8 x 40G/100G fiber ports
7520-48YE-8CE-AC-R	7520-48YE-8CE-AC-R with back-to- front airflow	Extreme 7520-48YE Switch - Ships with two AC back-to-front airflow power supplies, six back- to-front airflow fans, one 4-post rack mount kit. Supports 48 x 10G/25G fiber ports and 8 x 40G/100G fiber ports. Includes embedded MACsec capabilities.

Accessories

Part Number	Product Name	Description
XN-ACPWR-800W-F	800W AC PSU (Front-to-Back)	AC800W PSU, Front to Back Airflow for use in 7520, 7720
XN-ACPWR-800W-R	800W AC PSU (Back-to-Front)	AC800W PSU, Back to Front Airflow for use in 7520, 7720
XN-DCPWR-800W-F	800W DC PSU (Front-to-Back)	DC800W PSU, Front to Back Airflow for use in 7520, 7720
XN-DCPWR-800W-R	800W DC PSU (Back-to-Front)	DC800W PSU, Back to Front Airflow for use in 7520, 7720
XN-FAN-001-F	Fan Module (Front-to-Back)	Single fan module Front to Back Airflow (also used in X695, VSP 7400, SLX 9150, SLX 9250, 7720, 8520, and 8720)
XN-FAN-001-R	Fan Module (Back-to-Front)	Single fan module Back to Front Airflow (also used in X695, VSP 7400, SLX 9150, SLX 9250, 7720, 8520, and 8720)
XN-2P-RKMP299	Two-post rack mount kit	Two-post rack mount kit for 7520 and 7720 switches
XN-4P-RKMT298	Four-post rack mount kit	Four-post rack mount kit for 7520-48Y, 7520-48XT, and 7720 switches
XN-4P-RKMT302	Four-post rack mount kit	Four-post rack mount kit for 7520-48YE switches

Software Licenses

Part Number	Product Name	Description
7000-PRMR-LIC-P	Premier License for 7000 Series	Perpetual Premier License for Extreme 7000 series (Includes Integrated Application Hosting)
7000-MACSEC-LIC-P	MACsec License for 7000 Series	Perpetual MACsec License for Extreme 7000 series

Warranty

All 7520 Series models are covered under Extreme's Universal LLW policy. For warranty details, visit: <http://www.extremenetworks.com/support/policies>

Maintenance Services

Extreme's maintenance and support services with 100% in-sourced engineering experts and over 90% first-person resolution ensure efficient operation of your business-essential network. 24x7x365 phone support, advanced parts replacement, and on-site support augment your staff with experienced resources that help you mitigate critical network issues fast. Visit Extreme Maintenance Services for more information.

Optics / Transceivers

For a list of the optics/transceivers supported on the 7520 Series hardware, refer to our Extreme Optics Compatibility Tool at <https://optics.extremenetworks.com>.

Power Cords

In support of Extreme Networks green initiatives, power cords are not included with the 7520 but can be ordered separately. They should be specified at time of ordering.



©2023 Extreme Networks, Inc. All rights reserved. Extreme Networks and the Extreme Networks logo are trademarks or registered trademarks of Extreme Networks, Inc. in the United States and/or other countries. All other names are the property of their respective owners. For additional information on Extreme Networks Trademarks please see <http://www.extremenetworks.com/company/legal/trademarks>. Specifications and product availability are subject to change without notice. 7aug23